

PRODUCT INFORMATION PACKET

Model No: 108022.00

Catalog No: 108022.00

SCR Motor, 1 HP, 90 V, 1750 RPM, S56C Frame, TEFC



Regal and are trademarks of Regal Rexnord Corporation or one of its affiliated companies.
©2022 Regal Rexnord Corporation, All Rights Reserved. MC017097E

Nameplate Specifications




Output HP	1 Hp	Output KW	0.75 kW
Voltage	90 V	Current	10.0 A
Speed	1750 rpm	Service Factor	1
Efficiency	83.7 %	Duty	Continuous
Insulation Class	F	Frame	S56C
Enclosure	Totally Enclosed Fan Cooled	Thermal Protection	No Protection
Ambient Temperature	40 °C	Drive End Bearing Size	6203
Opp Drive End Bearing Size	6203	UL	Recognized
CSA	Y	CE	N

Technical Specifications

Rotation	Reversible	Mounting	Rigid C base
Overall Length	14.82 in	Frame Length	7.47 in
Shaft Diameter	0.625 in	Shaft Extension	2.06 in
Torque	36 LB-IN		
Outline Drawing	031879-108022	Connection Drawing	00531901

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:09/19/2022

RBC PROPRIETARY AND CONFIDENTIAL INFORMATION
This document is the property of REGAL BELOIT CORPORATION ("RBC") including its subsidiaries and divisions and contains proprietary information of RBC. This document is loaned to you on the express condition that neither the information contained herein shall be disclosed to others without the express written consent of RBC, and that the information shall be used by the recipient only as approved expressly by RBC. This document shall be returned to RBC upon its request. This document may be subject to certain restrictions under U.S. export control laws and regulations.



- NOTES:
1) MAXIMUM FACE RUNOUT .004 T.I.R.
2) MAXIMUM PILOT ECCENTRICITY .004 T.I.R.
3) PERMISSIBLE SHAFT RUNOUT .002 T.I.R.
4) GASKETS THROUGHOUT

109100.00	15.82	13.76	8.10	90	3/4	1140
109099.00	14.32	12.26	6.60	90	1/2	1140
109098.00	12.82	10.76	5.10	90	1/3	1140
108265.00	15.32	13.26	7.60	180	1 1/2	2500
108092.00	16.82	14.76	9.10	180	1 1/2	1750
108023.00	14.82	12.76	7.10	180	1	1750
108022.00	14.82	12.76	7.10	90	1	1750
108021.00	13.82	11.76	6.10	180	1	2500
108020.00	13.32	11.26	5.60	90	1	2500
108019.00	13.82	11.76	6.10	180	3/4	1750
108018.00	13.82	11.76	6.10	90	3/4	1750
108017.00	12.82	10.76	5.10	180	3/4	2500
108016.00	12.82	10.76	5.10	90	3/4	2500
108015.00	12.82	10.76	5.10	180	1/2	1750
108014.00	12.82	10.76	5.10	90	1/2	1750
CATALOG No.	"C"	"L"	"AD"	VOLTS	H.P.	RPM

06	CHANGED .06 & 1.94 DIMS TO REF., ISAAC 12-0984	IPG	1/30/2013		TOLERANCES UNLESS SPECIFIED				
05	ADDED NOTE ABOUT FAN GUARD LOCATION, ISAAC 09-4813	IPG	12/4/2009		DEC	INCHES			
04	CAT. # 108092.00: "C" WAS 17.32, "L" WAS 15.26, "AD" WAS 9.60, ISAAC 09-1828	IPG	5/14/2009	X		±.1			
03	ADDED DATA FOR VARIOUS CAT. NUMBERS, COMPLETED	IPG	9/15/2008	XXX		±.005			
	TABLE			XXXX		±.0005			
NO	REVISION	BY & DATE	CHK	ANG	±1/2°	FINISH			
			RFP			PREV			
	THIRD ANGLE PROJECTION								
					NETWORK FILE NAME	031879			
					SIZE	B	DRAWING NO	031879	REV
									06



ELECTRIC MOTORS
GEARMOTORS
AND DRIVES

DRAWN RWS 1/8/08
CHK IPG 1/9/08
APPR


TITLE OUTLINE
48 FRAME DC - S56C MOUNT

SCALE 1:2
REF 03189.00

FMF 108022.75

PAGE OF

005319.01




CONNECTIONS SHOWN FOR CCW ROTATION FACING LEAD END OF THE MOTOR
TO REVERSE ROTATION INTERCHANGE LINE LEADS

				TOLERANCES UNLESS SPECIFIED		 ELECTRIC MOTORS GEARMOTORS AND DRIVES	DRAWN TJF 11/15/97			
				DEC.	INCHES		CHK			
				.X	±.1		APPD POW 11/15/97			
E	"MOTOR" WAS "ARMATURE", ECO-0163602	IPG 3/14/19		.XX	±.01	TITLE EXTERNAL WIRING DIAGRAM PMDC MOTOR			SCALE 1=2	
D	UPDATED TO MAKE IT GENERIC, ECO-0163547	IPG 3/13/19		.XXX	±.005				REF	
01	REDRAWN ON CAD. REVISED NOTES.	SJB 9/20/2005		.XXXX	±.0005	MAT'L.			FMF	
NO.	REVISION	BY & DATE	CHK	ANG	±1/2"	FINISH			PREV	
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT – DO NOT SCALE THIS PRINT			RFP		CAD FILE 00531901		SIZE	DRAWING NO.		REV.
			DIST				A	005319.01		E

LEESON ELECTRIC CORPORATION

TYPICAL PERFORMANCE CURVE

FOR DIRECT CURRENT PERMANENT MAGNET MOTOR

Model No. C4D17FK5Catalog No. 108022.00HP 1.000RPM 1750DC Volts 90.0N.P. FLA 10.00F.F. 1.38Encl TEFCType DFS.F. 1.00Max. Amb. 40.0 Deg CInsul. FFrame S56CDuty Cont

Ra 0.4200 Ohms
 La 6.600 mHenrys
 Ja 14.40 LB-IN²
 Ke 46.33 V/KRPM

Kt 3.916 LB-IN/AMP
 I_{max} 103.1 AMPS Allowed
 FL Torque 36.00 LB-IN
 FL EFF 83.70 %

Winding W- D5621-1Prepared by S. BernhardtDate 05-06-2009