

NEMA

Model **SSBN0004D-C**
MFG PN: TSSN56HC1U4B

Model **SSBN0004D-C**

Product Data Package



MODEL	HP	RPM	VOLTAGE	PHASE	Hz	FRAME	MOUNT	ENCLOSURE
SSBN0004D-C	1	1760	230/460	3	60	56HC	Rigid/C-Flange	TENV

Toronto

TOLL FREE 1.888.286.1820
PHONE 905.829.1001
EMAIL info@techtopcanada.com

Montreal

TOLL FREE 1.844.354.5111
PHONE 514.354.1002
EMAIL infoQC@techtopcanada.com

Moncton

PHONE 506.386.5794
EMAIL infoNB@techtopcanada.com

Winnipeg

PHONE 204.633.2779
EMAIL infoMB@techtopcanada.com

Vancouver

PHONE 604.525.1551
EMAIL infoBC@techtopcanada.com



Index

Motor General Data Sheet	P 2
Nameplate Information	P 3
Technical Performance Data	P 4
Motor General Wiring Diagram	P 5
Motor General Outline Drawing	P 6

NEMA

Model SSBN0004D-C
MFG PN: TSSN56HC1U4B

ELECTRICAL DATA		
Rated Motor Output Power	1	HP
	0.75	kW
Rated Motor Speed	1760	r/min 60Hz
	1450	r/min 50Hz
Rated Motor Voltage (+/-10%)	230/460	V/60Hz
	190/380	V/50Hz
Rated Motor Current	3.18/1.59	A (I _n) @ 60Hz
	3.60/1.80	A (I _n) @ 50Hz
Phase	3	Ø
Locked Rotor Current @ High Voltage	-	A (I _n) @ 60Hz
FI Current @ 208V	3.52	A (I _n) @ 60Hz
Service Factor	1.25	@ 60Hz
	1	@ 50Hz
KVA Code	N	60Hz
	K	50Hz
Nominal Efficiency	86.5	% @ 60Hz
Nominal Power Factor	0.68	cosΦ @ 60Hz
Leads (Qty, Size)	9	18
Connection	YY/Y	-
Coil Resistance	-	Ω
Start Capacitor	-	μF/V
Run Capacitor	-	μF/V
VFD DUTY (S.F. 1.0)	RATIO	Hz
Variable Torque	30:1	2 - 60
Constant Torque	15:1	4 - 60
FULL LOAD TEMPERATURE RISE		
Full Load Temperature Rise	65.9	°C @ 60Hz
	-	°C @ 50Hz

GENERAL DATA		
Frame Size	56HC	
Enclosure	TENV	
Mounting	Rigid/C-Flange	
Approximate Weight (lbs.)	48.5 lbs.	
Casing Material / Fan Cover	Stainless Steel	Stainless Steel
Shaft Material	304 SS	
NEMA Design	B	
Degree of Protection (IP)	69K	
Insulation Class / Temp Rise (60Hz)	F	B
Tropicalization	YES	
Duty	Cont. / S1	
Conduit Box Location	F1	
Feet Removable / Double Drilled	NO	YES
Paintwork	unpainted	
	unpainted	
MECHANICAL DATA		
Bearing DE Side	6205 ZZ	
Bearing ODE Side	6204 ZZ	
Grease Type	Food grade Mobilgrease™ FM 222	
Compensation Ring (wavy washer)	NDE	
Moment of Inertia (lb-ft²)	-	
Sound Pressure @ 3 FT dBA	-	
SITE CONDITIONS		
Ambient Temperature (°C)	40	
Meters Above Sea Level (MASL)	1000	
HAZARDOUS LOCATIONS		
CSA Certified	A, B, C & D	
Temperature Code	-	-



Questions? Call 1.888.286.1820

DATA SHEET: THREE-PHASE SQUIRREL CAGE MOTOR
STAINLESS STEEL IP69K MOTORS



NEMA


Model SSBN0004D-C
MFG PN: TSSN56HC1U4B



HP	"C"
12P	11.6
14P	12.2

NAMEPLATE DATA	60Hz	50Hz
Horse Power	1	1
RPM	1760	1450
Voltage	230/460	190/380
Full Load Amps	3.18/1.59	3.60/1.80
Service Factor	1.25	1
KVA Code	N	K
Full Load Amps (208V)	3.52	-
Nominal Efficiency	86.5	85
Nominal Power Factor	0.68	0.74
Design	B	
Frame	56HC	
Enclosure Type	TENV	
IP Rating	69K	
Duty	Cont. / S1	
Insulation Class	F	
Ambient Rating	40	
Drive End Bearing	6205 ZZ	
Opposite Drive End Bearing	6204 ZZ	
Weight (lbs)	48.5	

NAMEPLATE LAYOUT



VFD DUTY (S.F. 1.0)	RATIO	Hz*
Variable Torque	30:1	2 - 60
Constant Torque	15:1	4 - 60

*For max speed please contact Techtop Canada


HAZARDOUS LOCATIONS	CSA COMPLIANT
Class / Division	Class I, Div. 2
Groups	A, B, C & D

Questions? Call 1.888.286.1820

NEMA

Model **SSBN0004D-C**
MFG PN: TSSN56HC1U4B

Torque Speed (T-n) Curve



PERFORMANCE LOAD VALUES, HIGH VOLTAGE, 60Hz

TORQUE VALUES	TORQUE (lb-ft)	TORQUE (% FULL LOAD)	PERFORMANCE VALUES	
Locked Rotor Torque	12.6	423	Start Configuration	DOL
Pull-Up Torque	11.7	393	Starting Current (A)	-
Breakdown Torque	15.5	518	No-Load Current (A)	1.2
Full Load Torque	3	100	No-Load Power Factor	-



TYPICAL PERFORMANCE - NOT GUARANTEED VALUES

% OF RATED LOAD	25	50	75	100	125	S.F. 1.25
Line Amperes (A)	1.2	1.3	1.4	1.6	1.8	1.8
Efficiency (%)	71.3	81.9	85.4	86.6	86.7	86.7
Speed (r/min)	1790	1780	1770	1759	1748	1748
Power Factor (cosΦ)	0.28	0.45	0.58	0.68	0.75	0.75
Input Power (kW)	0.26	0.46	0.66	0.87	1.08	1.08


Questions? Call 1.888.286.1820



Model **SSBN0004D-C**
MFG PN: TSSN56HC1U4B



HIGH VOLTAGE
(Y)




LOW VOLTAGE
(YY)

- NOTES:
- 1. CCW ROTATION FACING ODE FOR CONNECTIONS SHOWN
 - 2. TO REVERSE ROTATION, SWAP ANY TWO INPUT LINES
 - 3. WHEN MOTOR IS IN F1 POSITION, LEADS INDICATED WITH “*” EXIT THE CASING ABOVE THE CENTER LINE OF THE MOTOR, THE REMAINING LEADS EXIT BELOW THE CENTER LINE
 - 4. LEADS MUST BE NUMBERED AND COLORED AS SHOWN
 - 5. DIAGRAMS FOR REFERENCE ONLY




NEMA 3Ø YY/Y 9-Lead Dual Voltage

DRAWING NUMBER:	NEMA-3-9-YY-Y-SS	ISSUED DATE	24/02/25
CONNECTION:	YY/Y	STAINLESS STEEL IP69K MOTORS	
NUMBER OF LEADS:	9		
THERMAL PROTECTION:	-		



HP	"C"
1 2P	11.6
1 4P	12.2



NEMA Premium TENV 56HC

DRAWING NUMBER:	SS3-NV-56HC	ISSUED DATE	24/02/25
DIMENSIONS:	Inches	STAINLESS STEEL IP69K MOTORS	
MOUNTING:	Rigid/C-Flange		
CASING MATERIAL:	Stainless Steel		