

NEMA

Model **SSBN.754D-C**
MFG PN: TSSN56C3/4U4B

Model **SSBN.754D-C**

Product Data Package



MODEL	HP	RPM	VOLTAGE	PHASE	Hz	FRAME	MOUNT	ENCLOSURE
SSBN.754D-C	0.75	1760	230/460	3	60	56C	Rigid/C-Flange	TENV

Toronto

TOLL FREE 1.888.286.1820
PHONE 905.829.1001
EMAIL info@techtopcanada.com

Montreal

TOLL FREE 1.844.354.5111
PHONE 514.354.1002
EMAIL infoQC@techtopcanada.com

Moncton

PHONE 506.386.5794
EMAIL infoNB@techtopcanada.com

Winnipeg

PHONE 204.633.2779
EMAIL infoMB@techtopcanada.com

Vancouver

PHONE 604.525.1551
EMAIL infoBC@techtopcanada.com



Index

Motor General Data Sheet	P 2
Nameplate Information	P 3
Technical Performance Data	P 4
Motor General Wiring Diagram	P 5
Motor General Outline Drawing	P 6

NEMA

Model SSBN.754D-C
MFG PN: TSSN56C3/4U4B

ELECTRICAL DATA		
Rated Motor Output Power	0.75	HP
	0.55	kW
Rated Motor Speed	1760	r/min 60Hz
	1450	r/min 50Hz
Rated Motor Voltage (+/-10%)	230/460	V/60Hz
	190/380	V/50Hz
Rated Motor Current	2.42/1.21	A (I _n) @ 60Hz
	2.72/1.36	A (I _n) @ 50Hz
Phase	3	Ø
Locked Rotor Current @ High Voltage	10.06	A (I _n) @ 60Hz
FI Current @ 208V	2.67	A (I _n) @ 60Hz
Service Factor	1.25	@ 60Hz
	1	@ 50Hz
KVA Code	N	60Hz
	K	50Hz
Nominal Efficiency	85.5	% @ 60Hz
Nominal Power Factor	0.68	cosΦ @ 60Hz
Leads (Qty, Size)	9	18
Connection	YY/Y	—
Coil Resistance	-	Ω
Start Capacitor	-	µF/V
Run Capacitor	-	µF/V
VFD DUTY (S.F. 1.0)	RATIO	Hz
Variable Torque	30:1	2 - 60
Constant Torque	15:1	4 - 60
FULL LOAD TEMPERATURE RISE		
Full Load Temperature Rise	50.1	°C @ 60Hz
	-	°C @ 50Hz

GENERAL DATA		
Frame Size	56C	
Enclosure	TENV	
Mounting	Rigid/C-Flange	
Approximate Weight (lbs.)	43.2 lbs.	
Casing Material / Fan Cover	Stainless Steel	Stainless Steel
Shaft Material	304 SS	
NEMA Design	B	
Degree of Protection (IP)	69K	
Insulation Class / Temp Rise (60Hz)	F	B
Tropicalization	YES	
Duty	Cont. / S1	
Conduit Box Location	F1	
Feet Removable / Double Drilled	NO	NO
Paintwork	unpainted	
	unpainted	
MECHANICAL DATA		
Bearing DE Side	6205 ZZ	
Bearing ODE Side	6204 ZZ	
Grease Type	Food grade Mobilgrease™ FM 222	
Compensation Ring (wavy washer)	NDE	
Moment of Inertia (lb-ft²)	-	
Sound Pressure @ 3 FT dBA	-	
SITE CONDITIONS		
Ambient Temperature (°C)	40	
Meters Above Sea Level (MASL)	1000	
HAZARDOUS LOCATIONS		
CSA Certified	A, B, C & D	
Temperature Code	-	-


Questions? Call 1.888.286.1820

DATA SHEET: THREE-PHASE SQUIRREL CAGE MOTOR
STAINLESS STEEL IP69K MOTORS




NEMA

Model SSBN.754D-C
MFG PN: TSSN56C3/4U4B




HP	°C
0.5 2P	10.4
0.33 4P	10.4
0.5 4P	11
0.75 2P	11
0.75 4P	11.6



NAMEPLATE DATA	60Hz	50Hz
Horse Power	0.75	0.75
RPM	1760	1450
Voltage	230/460	190/380
Full Load Amps	2.42/1.21	2.72/1.36
Service Factor	1.25	1
KVA Code	N	K
Full Load Amps (208V)	2.67	-
Nominal Efficiency	85.5	84.5
Nominal Power Factor	0.68	0.74
Design	B	
Frame	56C	
Enclosure Type	TENV	
IP Rating	69K	
Duty	Cont. / S1	
Insulation Class	F	
Ambient Rating	40	
Drive End Bearing	6205 ZZ	
Opposite Drive End Bearing	6204 ZZ	
Weight (lbs)	43.2	

NAMEPLATE LAYOUT



VFD DUTY (S.F. 1.0)	RATIO	Hz*
Variable Torque	30:1	2 - 60
Constant Torque	15:1	4 - 60

*For max speed please contact Techtop Canada


HAZARDOUS LOCATIONS	CSA COMPLIANT
Class / Division	Class I, Div. 2
Groups	A, B, C & D

Questions? Call 1.888.286.1820

NEMA

Model SSBN.754D-C
MFG PN: TSSN56C3/4U4B

Torque Speed (T-n) Curve



PERFORMANCE LOAD VALUES, HIGH VOLTAGE, 60Hz

TORQUE VALUES	TORQUE (lb-ft)	TORQUE (% FULL LOAD)	PERFORMANCE VALUES	
Locked Rotor Torque	7.8	347	Start Configuration	DOL
Pull-Up Torque	7.1	319	Starting Current (A)	10.06
Breakdown Torque	10	446	No-Load Current (A)	0.8
Full Load Torque	2.2	100	No-Load Power Factor	0.08



TYPICAL PERFORMANCE - NOT GUARANTEED VALUES

% OF RATED LOAD	25	50	75	100	125	S.F. 1.25
Line Amperes (A)	0.8	0.9	1	1.2	1.3	1.3
Efficiency (%)	71.2	81.8	85.3	86.5	86.7	86.7
Speed (r/min)	1791	1783	1775	1766	1756	1756
Power Factor (cosΦ)	0.29	0.46	0.6	0.69	0.75	0.75
Input Power (kW)	0.2	0.34	0.49	0.65	0.81	0.81


Questions? Call 1.888.286.1820



Model **SSBN.754D-C**
MFG PN: TSSN56C3/4U4B



HIGH VOLTAGE
(Y)




LOW VOLTAGE
(YY)

- NOTES:
- 1. CCW ROTATION FACING ODE FOR CONNECTIONS SHOWN
 - 2. TO REVERSE ROTATION, SWAP ANY TWO INPUT LINES
 - 3. WHEN MOTOR IS IN F1 POSITION, LEADS INDICATED WITH “*” EXIT THE CASING ABOVE THE CENTER LINE OF THE MOTOR, THE REMAINING LEADS EXIT BELOW THE CENTER LINE
 - 4. LEADS MUST BE NUMBERED AND COLORED AS SHOWN
 - 5. DIAGRAMS FOR REFERENCE ONLY




NEMA 3Ø YY/Y 9-Lead Dual Voltage

DRAWING NUMBER:	NEMA-3-9-YY-Y-SS	ISSUED DATE	24/02/25
CONNECTION:	YY/Y	STAINLESS STEEL IP69K MOTORS	
NUMBER OF LEADS:	9		
THERMAL PROTECTION:	-		



HP	"C"
0.5 2P	10.4
0.33 4P	10.4
0.5 4P	11
0.75 2P	11
0.75 4P	11.6



NEMA Premium TENV 56C

DRAWING NUMBER:	SS3-NV-56C	ISSUED DATE	24/02/25
DIMENSIONS:	Inches		
MOUNTING:	Rigid/C-Flange		
CASING MATERIAL:	Stainless Steel		

STAINLESS STEEL IP69K MOTORS