

**NEMA**

Model **SSG0034FS-TC**  
MFG PN: TSSF140TC3U4B

# Model **SSG0034FS-TC**

## Product Data Package



| MODEL        | HP | RPM  | VOLTAGE | PHASE | Hz | FRAME | MOUNT          | ENCLOSURE |
|--------------|----|------|---------|-------|----|-------|----------------|-----------|
| SSG0034FS-TC | 3  | 1750 | 575     | 3     | 60 | 140TC | Rigid/C-Flange | TEFC      |

### Toronto

TOLL FREE 1.888.286.1820  
PHONE 905.829.1001  
EMAIL [info@techtopcanada.com](mailto:info@techtopcanada.com)

### Montreal

TOLL FREE 1.844.354.5111  
PHONE 514.354.1002  
EMAIL [infoQC@techtopcanada.com](mailto:infoQC@techtopcanada.com)

### Moncton

PHONE 506.386.5794  
EMAIL [infoNB@techtopcanada.com](mailto:infoNB@techtopcanada.com)

### Winnipeg

PHONE 204.633.2779  
EMAIL [infoMB@techtopcanada.com](mailto:infoMB@techtopcanada.com)

### Vancouver

PHONE 604.525.1551  
EMAIL [infoBC@techtopcanada.com](mailto:infoBC@techtopcanada.com)



### Index

|                               |     |
|-------------------------------|-----|
| Motor General Data Sheet      | P 2 |
| Nameplate Information         | P 3 |
| Technical Performance Data    | P 4 |
| Motor General Wiring Diagram  | P 5 |
| Motor General Outline Drawing | P 6 |

**NEMA**

**Model SSG0034FS-TC**  
**MFG PN: TSSF140TC3U4B**

| ELECTRICAL DATA                     |              |                            |
|-------------------------------------|--------------|----------------------------|
| Rated Motor Output Power            | 3            | HP                         |
|                                     | 2.2          | kW                         |
| Rated Motor Speed                   | 1750         | r/min 60Hz                 |
|                                     | -            | r/min 50Hz                 |
| Rated Motor Voltage (+/-10%)        | 575          | V/60Hz                     |
|                                     | -            | V/50Hz                     |
| Rated Motor Current                 | 3.35         | A (I <sub>n</sub> ) @ 60Hz |
|                                     | -            | A (I <sub>n</sub> ) @ 50Hz |
| Phase                               | 3            | Ø                          |
| Locked Rotor Current @ High Voltage | -            | A (I <sub>n</sub> ) @ 60Hz |
| FI Current @ 208V                   | -            | A (I <sub>n</sub> ) @ 60Hz |
| Service Factor                      | 1.25         | @ 60Hz                     |
|                                     | -            | @ 50Hz                     |
| KVA Code                            | L            | 60Hz                       |
|                                     | -            | 50Hz                       |
| Nominal Efficiency                  | 89.5         | % @ 60Hz                   |
| Nominal Power Factor                | 0.75         | cosΦ @ 60Hz                |
| Leads (Qty, Size)                   | 3            | 18                         |
| Connection                          | Y            | -                          |
| Coil Resistance                     | -            | Ω                          |
| Start Capacitor                     | -            | µF/V                       |
| Run Capacitor                       | -            | µF/V                       |
| <b>VFD DUTY (S.F. 1.0)</b>          | <b>RATIO</b> | <b>Hz</b>                  |
| Variable Torque                     | 30:1         | 2 - 60                     |
| Constant Torque                     | 15:1         | 4 - 60                     |
| FULL LOAD TEMPERATURE RISE          |              |                            |
| Full Load Temperature Rise          | 67.7         | °C @ 60Hz                  |
|                                     | -            | °C @ 50Hz                  |

| GENERAL DATA                        |                                |                 |
|-------------------------------------|--------------------------------|-----------------|
| Frame Size                          | 140TC                          |                 |
| Enclosure                           | TEFC                           |                 |
| Mounting                            | Rigid/C-Flange                 |                 |
| Approximate Weight (lbs.)           | 69.5 lbs.                      |                 |
| Casing Material / Fan Cover         | Stainless Steel                | Stainless Steel |
| Shaft Material                      | 304 SS                         |                 |
| NEMA Design                         | B                              |                 |
| Degree of Protection (IP)           | 69K                            |                 |
| Insulation Class / Temp Rise (60Hz) | F                              | B               |
| Tropicalization                     | YES                            |                 |
| Duty                                | Cont. / S1                     |                 |
| Conduit Box Location                | F1                             |                 |
| Feet Removable / Double Drilled     | NO                             | YES             |
| Paintwork                           | unpainted                      |                 |
|                                     | unpainted                      |                 |
| MECHANICAL DATA                     |                                |                 |
| Bearing DE Side                     | 6205 ZZ                        |                 |
| Bearing ODE Side                    | 6204 ZZ                        |                 |
| Grease Type                         | Food grade Mobilgrease™ FM 222 |                 |
| Compensation Ring (wavy washer)     | NDE                            |                 |
| Moment of Inertia (lb-ft²)          | -                              |                 |
| Sound Pressure @ 3 FT dBA           | -                              |                 |
| SITE CONDITIONS                     |                                |                 |
| Ambient Temperature (°C)            | 40                             |                 |
| Meters Above Sea Level (MASL)       | 1000                           |                 |
| HAZARDOUS LOCATIONS                 |                                |                 |
| CSA Certified                       | A, B, C & D                    |                 |
| Temperature Code                    | -                              | -               |


**Questions? Call 1.888.286.1820**

**DATA SHEET: THREE-PHASE SQUIRREL CAGE MOTOR**  
**STAINLESS STEEL IP69K MOTORS**



**NEMA**

**Model SSG0034FS-TC**  
**MFG PN: TSSF140TC3U4B**



| NAMEPLATE DATA             | 60Hz       | 50Hz |
|----------------------------|------------|------|
| Horse Power                | 3          | -    |
| RPM                        | 1750       | -    |
| Voltage                    | 575        | -    |
| Full Load Amps             | 3.35       | -    |
| Service Factor             | 1.25       | -    |
| KVA Code                   | L          | -    |
| Full Load Amps (208V)      | -          | -    |
| Nominal Efficiency         | 89.5       | -    |
| Nominal Power Factor       | 0.75       | -    |
| Design                     | B          |      |
| Frame                      | 140TC      |      |
| Enclosure Type             | TEFC       |      |
| IP Rating                  | 69K        |      |
| Duty                       | Cont. / S1 |      |
| Insulation Class           | F          |      |
| Ambient Rating             | 40         |      |
| Drive End Bearing          | 6205 ZZ    |      |
| Opposite Drive End Bearing | 6204 ZZ    |      |
| Weight (lbs)               | 69.5       |      |

**NAMEPLATE LAYOUT**

**TECHTOP** STAINLESS STEEL ELECTRIC MOTOR WASHDOWN DUTY BISSC CERTIFIED (IP69K)

MODEL PH 3 ENCL 60 FRAME 50 IP69K MFG PN

DATE SER#

DESIGN INS CL

DUTY AMB

WEIGHT lbs.

DE BRG

ODE BRG

CONNECTION DIAGRAM

T1 T2 T3

L1 L2 L3

LINE

TO REVERSE ROTATION INTERCHANGE ANY TWO LINE LEADS

INVERTER DUTY

15:1 CONSTANT TORQUE

90:1 VARIABLE TORQUE

0.75 SERVICE FACTOR

MADE IN CHINA

CE

NEMA Premium

E323353

224663

CLASS 1, DIV 2, GROUPS A, B, C AND D COMPLIANT

USABLE AT 208V 60HZ FLA:

**VFD DUTY (S.F. 1.0)**

Variable Torque

Constant Torque

**RATIO**

30:1

15:1

**Hz\***

2 - 60

4 - 60

\*For max speed please contact Techtop Canada

**HAZARDOUS LOCATIONS**

Class / Division

Groups

**CSA COMPLIANT**

Class I, Div. 2


A, B, C & D

**Questions? Call 1.888.286.1820**

**NEMA**

**Model SSG0034FS-TC**  
MFG PN: TSSF140TC3U4B

**Torque Speed (T-n) Curve**



**PERFORMANCE LOAD VALUES, HIGH VOLTAGE, 60Hz**

| TORQUE VALUES       | TORQUE (lb-ft) | TORQUE (% FULL LOAD) | PERFORMANCE VALUES   |     |
|---------------------|----------------|----------------------|----------------------|-----|
| Locked Rotor Torque | 28.4           | 315                  | Start Configuration  | DOL |
| Pull-Up Torque      | 24.5           | 272                  | Starting Current (A) | -   |
| Breakdown Torque    | 35.5           | 394                  | No-Load Current (A)  | 2.1 |
| Full Load Torque    | 9              | 100                  | No-Load Power Factor | -   |



**TYPICAL PERFORMANCE - NOT GUARANTEED VALUES**

| % OF RATED LOAD     | 25   | 50   | 75   | 100  | 125  | S.F. 1.25 |
|---------------------|------|------|------|------|------|-----------|
| Line Amperes (A)    | 2.2  | 2.4  | 2.8  | 3.3  | 3.9  | 3.9       |
| Efficiency (%)      | 78.1 | 85.8 | 87.6 | 87.7 | 86.9 | 86.9      |
| Speed (r/min)       | 1788 | 1777 | 1764 | 1751 | 1736 | 1736      |
| Power Factor (cosΦ) | 0.33 | 0.53 | 0.67 | 0.76 | 0.81 | 0.81      |
| Input Power (kW)    | 0.7  | 1.28 | 1.88 | 2.51 | 3.17 | 3.17      |

Questions? Call 1.888.286.1820



Model **SSG0034FS-TC**  
MFG PN: TSSF140TC3U4B




- NOTES:
- 1. CCW ROTATION FACING ODE FOR CONNECTIONS SHOWN
  - 2. TO REVERSE ROTATION, SWAP ANY TWO INPUT LINES
  - 3. WHEN MOTOR IS IN F1 POSITION, LEADS INDICATED WITH “\*” EXIT THE CASING ABOVE THE CENTER LINE OF THE MOTOR, THE REMAINING LEADS EXIT BELOW THE CENTER LINE
  - 4. LEADS MUST BE NUMBERED AND COLORED AS SHOWN
  - 5. DIAGRAMS FOR REFERENCE ONLY



|                     |               |
|---------------------|---------------|
| DRAWING NUMBER:     | NEMA-3-3-Y-SS |
| CONNECTION:         | Y             |
| NUMBER OF LEADS:    | 3             |
| THERMAL PROTECTION: | -             |

NEMA 3Ø Y 3-Lead Single Voltage

|                              |          |
|------------------------------|----------|
| ISSUED DATE                  | 24/02/25 |
| STAINLESS STEEL IP69K MOTORS |          |



NEMA Premium TEFC 140TC

|                  |                 |             |                              |
|------------------|-----------------|-------------|------------------------------|
| DRAWING NUMBER:  | SS3-TF-140TC    | ISSUED DATE | 24/02/25                     |
| DIMENSIONS:      | Inches          |             |                              |
| MOUNTING:        | Rigid/C-Flange  |             |                              |
| CASING MATERIAL: | Stainless Steel |             | STAINLESS STEEL IP69K MOTORS |